Work Order ID 100141 Thursday, April 18, 2013 10:34:33 AM				*	100	141*							Page 1	l
Revision ID:	D3997-31 Placard		A	Accept		*N900	040	100)*	Setup	Start Stop	*N *N	S1* S2*	:
Start Date: Required Date: Reference:	4/18/2013 4/25/2013	Start Qty: 10.00 Req'd Qty: 10.00	*10* *10*			Cust Item I Customer:	D:							
Approvals:	Process Pla	an: MF	Date: 13-4-18.	Tooling	:	D:	ate:			Run	Start	*N	R1*	
	QC:		Date:	SPC (Y	/N):		ate:				Stop	*N	R2*	
Sequence ID/ Work Center ID)	Operation Description		Set U Run	p/ Hours	Tool ID	Tool #	Plan Code	Accept Qty	Rej: Qty		Reject Number	Insp. Stamp	
Draw Nbr	Rev	ision Nbr					· · · · · · · · · · · · · · · · · · ·						· • · · · · · · · · · · · · · · · · · ·	
D3997	Α													
*100 *100* Purchasing Purchasing		Possible Supp	as per Dwg D3997 plier:Studio Lettrage ase note required	0.00							J	V 13-	04-1.	
*110 *110* Packaging Packaging		Receive & Inspect for Dan Memo	mage & Mat'l Certs	0.00							/4] 3/4/	be Co	
120 *120 QC Ouality Control		QC6- Inspect dimensions Memo	to drawing	0.00	134	,)6			8					

Quality Control

							İ					DQA:		Date:	1.
NCR:	es/	/ No				WOR	K ORDER NON-C	O	NFOR	MANCE / UPDATE		•		T ·	
											C	(A Closed:		Date:	
Work Orde	er:						DISPOSITION			AGAINST	DEP	ARTMENT	PROCI	 	
Part N	_						Rework Scrap			Skid-tube Crosstube Machining Small Fab noforming Finishing		Prod Rec/Stor	d. Eng.	1	Engineering Quality Other
NCR N	lo				·	Wo	Use-as-is ork Order Update			noforming Finishing Large Fab Composite		Rec/Stor		pplier	Other
Root					Descri	ption of v	vork order update	ı	nitial	Action .		Sign &			
Cause		Date	Step	Qty	C	or Non-co	onformance	Ch	ief Eng	Description		Date	Veri	fication	QC Inspector
oc/Data													į	,	
quip/Tooling	_					j									
perator	_					ļ								1	
1aterial	_					[1	
etup	_					i									
ther	_					į								1	
rocess	4					İ								1	
upplier	_					j i								' .	
raining	-					i								1	
Inapproved								<u> </u>	T CATE	CODY			1		
Landii						1	General	401	CATE	GURT					
Lanun		Bending			·	Bend	General		Grain	1	\Box	Ovalized	i	i i	Pressure/Forced
	_	Centre No	t Concer	tric to O/	, -	BOM/Ro	nute		Hardwa	ro	—	Over/Under	toleran	ce	Temperature/Cure
	─ ┤	Cracks	Concer	11.10 to 07.	~ -	d í	Damaged	\vdash	Į.	ion Incomplete	\vdash	art Incorre	- 1		Weld
		Crushed/C	rimped			Burrs	Damagea	\vdash	1	ions Incomplete/Unclear		art Lost/Mi		-	Wrong Stock Pulled
		Cuffs	pcu,			Contamir	nation		Mainte	· ·		art Moved	j]
		deat Treat	t			Counter			Mislabe			ositioned V	l Vrong		
ľ		nspection		Tube		Cut Too S			Misread			ower Loss/	- i		Other
	_	Ripples in				Drill Hol			Offset				ĺ	· · • · · · · · · · · · · · · · · · · ·	
	— 1	orque Wa		xtrusion		Drawing			4	Calibration	-		Ī		
	_	· Furning Se				4 1 7		Out of Sequence							
		Nave/Twi	•	e				Outside	Dimensions	_		i			

H:/FORMS/Quality Assurance\approved QA/NCRWO Rev G

Work Ord Thursday, April				*100	141*						Page 2
Item ID: Revision ID: Item Name:	D3997-31 Placard			Accept	*N9000	40100)*	Setup	Start Stop	I VI.	S1* S2*
Start Date: Required Date Reference:	4/18/2013 e: 4/25/2013	Start Qty: 10.00 Req'd Qty: 10.00	*10* *10*		Cust Item ID: Customer:					IV.	
Approvals:	Process Pl	an:	Date:	Tooling:	Date:			Run	Start	*N	R1*
	QC:		Date:	SPC (Y/N):	Date:				Stop	*N	R2*
Sequence ID/ Work Center I 130 *120* Packaging Packaging	ID	Operation Description Identify as per dwg & Stoc	sk Location:	Set Up/ Run Hours 0.00	Teol ID T	ool # Plan Code	Accep Qty	ot Re	-	Reject Number	Insp. Stamp
140 *140* QC Quality Control		QC21- Final Inspection - V Memo	Vork Order Release	0.00					13/	5 K	; 4

MF 13429

					ı .				DQA:	Date	
NCR: Y	es / No				WORK ORDER NON-	CONFOR	RMANCE / UP	PDATE	QA Closed:	Date	;
Work Orde	ır·				DISPOSITION			AGAINST DE	PARTMENT	/PROCESS	
Part N	0				Rework Scrap Use-as-is Work Order Update	The	Skid-tube Machining rmoforming Large Fab	Crosstube Small Fab Finishing Composite	⊣	Water Jet od. Eng. Coor. re/Packaging Supplier	Engineering Quality Other
Root					ption of work order update	Initial		ction	Sign & Date		
Cause	Date	Step	Qty		or Non-conformance	Chief En	nief Eng Description			Verification	QC Inspector
Doc/Data					İ						
quip/Tooling					ı						`
Operator					4					1	
Material					ı						
Setup					i	:] [
Other					į						
Process					1						
Supplier											
Training					T.						
Jnapproved					1						
						FAULT CAT	EGORY			<u> </u>	
Landin	g Gear				General				_		
	Bending				Bend	Grain	ı		Ovalized	!	Pressure/Forced
	Centre No	ot Conce	ntric to	o/s	BOM/Route	Hardv	vare		Over/Under	tolerance	Temperature/Cure
	Cracks				Broken/Damaged	Inspe	ction Incomplete		Part Incorre	ect	Weld
	Crushed/	Crimped.			Burrs	Instru	ctions Incomplete	/Unclear	Part Lost/M	lissing	Wrong Stock Pulled
	Cuffs				Contamination	Main	tenance		Part Moved	_	
ľ	Heat Trea	at			Countersink	Misla	→			Wrong	
	Inspectio	n Strip in	Tube		Cut Too Short	Misre	Misread Power Loss/S			/Surge	Other
Ī	Ripples in	n Bend			Drill Holes	Offse	Offset				

Out of Calibration

Out of Sequence

Outside Dimensions

H:/FORMS/Quality Assurance\approved QA/NCRWO Rev G

Turning Sequence Wave/Twist in Tube

Torque Waves in Extrusion

Drawing

Finish

Folio

Picklist Print

- Thursday, April 18, 2013 10:34:32 AM

Work Order ID:

100141

Parent Item:

D3997-31

Parent Item Name:

Placard

Start Date: 4/18/2013

Required Date: 4/25/2013

Page 1

Start Qty: 10.00

Required Qty: 10.00

Comments:

IPP rev A 10.01.13 new issue Prelim EC verified by:DD

Component Item ID/ Item Name	Replacement Item ID	Mfg/ Purch	Bin Item	Primary Location	Last Location	Route Seq ID	Unit of Measure	Qty on Hand	Qty per Kit	Total Qty	Qty Issued	Date Issued	Status	
D3997-31P		Purchased	No			*	Each	0.0000		10				-
	item ID			Location	Location	Seq ID					Issued	Issued		

/43/4/se (w)

										DQA:	Date:	•
NCR: \	res / No				WORK ORDER NON-	CON	IFOR N	MANCE / UP	DATE	QA Closed:	Date:	
Work Orde	nr:				DISPOSITION				AGAINST DE			
Part N	No				Rework Scrap Use-as-is Work Order Update		Skid-tube Crosstube Machining Small Fab Thermoforming Finishing Large Fab Composite			-}	Water Jet d. Eng. Coor. e/Packaging Supplier	Engineering Quality Other
Root	T	T		Descri	iption of work order update	l ir	nitial	Ac	tion	Sign &		
Cause	Date	Step	Qty		or Non-conformance		ief Eng Description			Date	Verification	QC Inspector
Doc/Data Equip/Tooling Operator Material Setup Other Process Supplier Training												
						AULT	CATE	GORY				
Landir	Bending Centre No Cracks Crushed/ Cuffs Heat Trea Inspectio Ripples in	Crimped at n Strip in n Bend	Tube		General Bend BOM/Route Broken/Damaged Burrs Contamination Countersink Cut Too Short Drill Holes		Instruct Mainte Mislabe Misread Offset	on Incomplete ions Incomplete/ nance led I	/Unclear	Ovalized Over/Under Part Incorre Part Lost/M Part Moved Positioned V Power Loss/	ct ssing Vrong	Pressure/Forced Temperature/Cure Weld Wrong Stock Pulled Other
	Torque W	aves in E	Extrusio	n .	Drawing	1 1	Out of (Calibration		•		

Out of Sequence


Outside Dimensions

H:/FORMS/Quality Assurance\approved QA/NCRWO Rev G

Turning Sequence


Wave/Twist in Tube

Finish Folio







D3997-29 PLACARD




D3997-33 PLACARD

NOTES:
1) MATERIAL: 3M 7 MIL MASKING FILM #8522CP OR AVERY IPM #2031
2) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
3) UNITS: INCHES UNLESS OTHERWISE NOTED
4) 36 PT BOLD FONT, RED TEXT ON WHITE BACKGROUND
5) 6 PT FONT, BLACK TEXT ON WHITE BACKGROUND
6) 24 PT BOLD FONT, BLACK TEXT ON WHITE BACKGROUND
7) 10 PT FONT, WHITE TEXT ON BLACK BACKGROUND
8) 9 PT BOLD FONT, WHITE TEXT ON BLACK BACKGROUND
9) 12 PT FONT, WHITE TEXT ON BLACK BACKGROUND
10) 6 PT FONT, WHITE TEXT ON BLACK BACKGROUND





D3997-31 PLACARD



D3997-35 PLACARD



DESIGN	8 5	DART AERO	SPACELID				
DRAWN	\$	HAWKESBURY, ON					
CHECKED	4	DRAWING NO.	REV. A				
MFG. APPR.	B	D3997	SHEET 5 OF 6				
APPROVED	#	TILE	SCALE				
DE APPR.	A	PLACARD	NTS				
DATE 09.1	0.05	COPYRIGHT © 2009 BY DART AEROSPACE LTD THE DOCUMENT OF PRIVATE AND CONFIDENTIA, AND IS EMPTIFED ON THE DUMESTS CONDITION THAT IT IS NOT TO BE USED FOR ANY PARPOCE OR COMED OR COMMUNICATED TO ANY GIVER PERSON WITHOUT					

3

5

5

4

8

2

										DQA:	····	Date:	
NCR: Y	es / No				WORK ORDER NON-C	CONF	ORN	MANCE / UPDATE		QA Closed:		Date:	
	····			T	,	- -							
Work Orde	er:				DISPOSITION			AGAIN	IST DE	PARTMENT	PROCE	SS	
					Rework] [Skid-tube Crosstu			i	er Jet 🗌	Engineering
Part N	lo				Scrap			Machining Small F	_		d. Eng.		Quality
NCR N	lo				Use-as-is Work Order Update	T		noforming Finishi Large Fab Compos	- - -		e/Pack Sur	aging	Other
Root				Descripti	ion of work order update	Init	ial	Action		Sign &	i		
Cause	Date	Step	Qty	or	Non-conformance	Chief	Eng	Description		Date	Verif	ication	QC Inspector
Doc/Data					1								
quip/Tooling					:						[
Operator		}											
Material													
Setup				,	!								
Other													
Process	_		· .		·	ļ					j		
Supplier					1								
Training	_				t ·								
Jnapproved		<u> </u>	ļ.,.,		· · · · · · · · · · · · · · · · · · ·	<u> </u>				L			
				<u></u>	`			GORY			<u>. </u>	·	
Landir F	ng Gear				General				Γ	Ovalized			Pressure/Forced
}	Bending			⊢	Bend BOM/Route				-	4			1
}	Centre No	ot Concer	ntric to	<u> </u>	-			re		Over/Under	1	ce	Temperature/Cure
}	Cracks	c : !		 	Broken/Damaged		•	on Incomplete	-	Part Incorred Part Lost/Mi	- 1	-	Weld Wrong Stock Pulled
}	Crushed/	Crimped.			Burrs			→ ⊢			ssing	ļL	I wrong Stock Pulled
}	Cuffs			 - 	Contamination		⊣ ' ⊢			Part Moved	Vrong		
}	Heat Trea		- 1	—	Countersink				\vdash	Positioned V	4 =		Other
1	Inspection	n Strip in	Tube	L_]c	Cut Too Short			Misread Power			surge		Other

Offset

Out of Calibration

Out of Sequence

Outside Dimensions

H:/FORMS/Quality Assurance\approved QA/NCRWO Rev G

Ripples in Bend

Turning Sequence

Wave/Twist in Tube

Torque Waves in Extrusion

Drill Holes

Drawing

Finish

Folio

****Certificate of Conformity****	
Customer:	
Studio Lettrege	
Purchase Order #: Packing Slip #: Part#: See dex	
	. 1 .
D3997-380-X10, D3997-37PXIZ D39977-21PXIO D3997	NIC.
D3997-15X10 D3997-19X12 D3997-23PX10 Certification:	
We hereby certify that:	
The above the listed items were manufactured, repaired and/or inspected in	
accordance with applicable drawings and/or specifications;	
All work was accomplished in accordance with the Dart Aerospace Purchase Order:	
Results of all inspections, chemical or physical tests, as well as other evidence, which shows the acceptability of raw materials, parts and/or assembly	
components are on file and available for inspection at any time.	
Authority:	
2m	
APPROVAL: 1/0 0= 25 F & AR MOATE:	
APPROVAL: KAPEN STE. MARIEDATE:	
Signature: Over B. Me	
Signature. 1010/Co.C., 1100	
Title: Resident Coordinator April 24 2013	
The project Colored Co	

Studio de Lettrage 210 Main Street W Hawkesbury, Ontario K6A 2H6

INVOICE

Invoice No.:

19942

Date:

04/25/2013

Ship Date:

Page:

Re: Order No.

WO9730

Sold to:

part Aerospace Ltd

1270 Aberdeen Hawkesbury, Ontario K6A 1K7

Ship to:

Dart Aerospace Ltd

Hawkesbury, Ontario

82500-7651 RT0001

Business No.:	82500 7651 RT	0001	The second of th	15 (1)		
Item No	Unit	Quantity	Description	Tax	Junit Price	Amount
		10 1 10 1 12 1 12 1 10 10 1 10 10 10	3M STICKER D3997-31P SET UP 3M STICKER D3997-35P SET UP 3M STICKER D3997-37P SET UP 3M STICKER D3997-1P SET UP 3M STICKER D3997-15P SET UP 3M STICKER D3997-21P SET UP 3M STICKER D3997-21P SET UP 3M STICKER D3997-21P SET UP 3M STICKER D3997-41P SET UP 7M STICKER D3997-41P SET UP 8M STICKER D3997-41P SET UP 9M STICKER D3997-41P SET UP PO#19617 H - HST 13% HST		2.5000 50.0000 2.5000 50.0000 2.0833 50.0000 2.0833 50.0000 2.5000 50.0000 2.5000 50.0000 2.5000 50.0000	25.00 50.00 25.00 50.00 25.00 50.00 25.00 50.00 25.00 50.00 25.00 50.00 25.00 78.00
Chudia da Lattraca	 	T-0001				
Studio de Lettrage Shipped By: Comment:	Tracking 1			1	Total Amount	678.00
Sold By:						

Studio de Lettrage 210 Main Street W Hawkesbury, Ontario K6A 2H6

INVOICE

Invoice No.:

19942

Date:

04/25/2013

Ship Date:

Page:

Re: Order No.

WO9730

Sold to:

part Aerospace Ltd

1270 Aberdeen

Hawkesbury, Ontario K6A 1K7

Ship to:

Dart Aerospace Ltd

Hawkesbury, Ontario

Business No.:

82500 7651 RT0001

Business No.:	82500 7651 RT0	1001	A STANDARD CONTRACTOR OF THE STANDARD CONTRACTOR	Ambuna at a se	Company of the Compan	*
Item No.	renge / Unit ->	· Quantity	Description	Tax	"Unit Price	Amount
		10 12 11 12 1 10 10 11 10 10	3M-STICKER D3997-31P SET UP 3M STICKER D3997-35P SET UP 3M STICKER D3997-37P SET UP 3M STICKER D3997-1P SET UP 3M STICKER D3997-15P SET UP 3M STICKER D3997-21P SET UP 3M STICKER D3997-21P SET UP 3M STICKER D3997-24P SET UP 3M STICKER D3997-41P SET UP PO#19617	***************************************	2.5000 50.0000 2.5000 50.0000 2.0833 50.0000 50.0000 2.5000 50.0000 2.5000 50.0000 2.5000 50.0000	25.00 50.00 25.00 50.00 25.00 50.00 25.00 50.00 25.00 50.00 25.00 50.00 25.00
Angeles of the second s	·		H - HST 13% HST			78.00
		· · · · · · · · · · · · · · · · · · ·				
Studio de Lettrage				<u> </u>	The Market State of the Control of t	
Shipped By: Comment: Sold By:	Tracking N	iumber:			Total Amount	678.0

3M

Product & Instruction Bulletin 8522

Release I, Effective September 2008 See Bulletin Change Summary and end of Bulletin This Bulletin now includes Instruction Bulletin 4.23

Scotchcal[™] Changeable Opaque Imaging Media

8522

Product Description

Recommended Types of Graphics and End Uses

For Thermal Inkjet Printing

This durable, 7 mil, opaque, changeable film is optimized for use with selected thermal inkjet printers and inks. Ink dries quickly on the film. When overlaminated, it is warranted for medium term, outdoor weatherable graphics, and long term indoor graphics.

When constructed and used as described in this Bulletin, these types of graphics and end uses may be warranted by the $3M^m$ MCS m Warranty. Please read the entire Bulletin for details.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
 - Graphics for vans, personal vehicles, trucks and buses
 - Novelty posters
 - Retail and point-of-purchase displays
 - Information graphics such as maps and directories
 - Entertainment promotions in museums, zoos, parks, theatres, sports venues
 - Education and presentation graphics
 - Legal and courtroom exhibits
- For flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications

Limitations of End Uses

3M specifically does not recommend or warrant the following uses, but please contact us to discuss your needs or recommend other products.

Unsuitable End Uses for This Product

- Not for electronically cut individual letters and numbers
- · Fleet applications in areas that use salt for winter road maintenance
- Application to non-warranted substrates, including wallboard
- Applications subjected to gasoline vapors or spills
- Application to corrugated or highly irregular surfaces or sharply raised areas
- Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.
- Graphics made for automotive Original Equipment Manufacturers (OEM); contact 3M Automotive Division at 1-800-328-1684 for alternatives.

About Water-Based Inkjet Technology

Standard inkjet technology is water based. Water-based chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication, Shelf Life and Storage sections in this Bulletin. Staying in the middle of these ranges always provides optimum performance.

Compatible Products

3M Graphic Materials

For complete details about graphic construction options, recommended uses and durability, refer to the Product Bulletin for the base film or substrate (media) you are using. See **3M Related Literature** at the end of this Bulletin.

This Bulletin provides details about the base film and construction options and warranty. Additional specific information about compatible products can be found in the Product and Instruction Bulletins listed in **3M Related Literature** at the end of this bulletin.

3M Graphic Materials

For complete details about graphic construction options, recommended uses and durability, refer to the Product Bulletin for the base film or substrate (media) you are using. See **3M Related Literature** at the end of this Bulletin.

Film

3M[™] Scotchcal[™] Opaque Imaging Media 8522

Overlaminate

- 3M™ Scotchcal™ Luster Overlaminate 8519
- 3M™ Scotchcal™ Matte Overlaminate 8520

Printers and Inks

HP Designjet Printers	HP Inks
 2500CP and 2000CP 2800CP and 3800CP 3500CP and 3000CP HP Designjet 5000 and 5500 	 Designjet CP Ink System UV (pigment-based) Designjet CP Inkjet System (imaging ink)
• Z6100	HP 91 Vivera Ink System

Epson Printers	Epson Inks		
Stylus Pro 9500	Archival Inks		
 Stylus Pro 10000 printer 	,		
Stylus Pro 10600 printer			

Characteristics

These are typical values for unprocessed product; processing may change the values. Contact your 3M representative for a custom specification.

Characteristic	Description			
Media	7 mil, white, opaque graphic film			
Liner	Low-slippage, lay flat paper			
Adhesive	Changeable, pressure sensitive			
Thickness	Media with adhesive: 7.5 to 8 mil (nominal)			
Warranted application substrates	See next page.			
Application surfaces	Flat or simple curved surfaces, with or without rivets, used in vertic (± 10°) applications (no corrugations)			
Application temperature range	28° to 110°F (-2° to 43°C) (air and surface)			
Removable	For up to one year; see Warranty Information			

Characteristic	Description			
Warranted application substrates	Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.			
	Alodine (anodized aluminum)			
	Automotive panels (automotive painted steel)			
	Fruehauf (painted aluminum)			
	FRP (fiberglass reinforced plywood)			
	• Glass			
	Imron ® (polyurethane-painted metal panel)			
	Acrylic			
	Sintra ™ board			
	Note: Use on any other substrate is strictly on a graphics manufacturer and customer test and approve basis. Test for both adhesion and removal characteristics. The plasticizer in some banner materials may migrate. This may cause the edge of the graphic to peel or lift off of the banner. For optimum performance, follow the guidelines in the section, Creating A Laminated Overlap, on page 4.			

Warranty Information

The warranty given in the Product Bulletin that is current at the time you purchased the film is the one that 3M will honor. The warranties in the following table(s), given in years, are for finished graphics exposed in a vertical exposure in the United States except the Desert Southwest. See the warranty sections following this table for additional information.

3M[™] MCS[™] Warranty Durability for Finished Graphics

Construction (film and overlaminate on	HP Printers & Inks		Epson Printers & Inks		Removal
warranted substrate	Outdoor	Indoor	Outdoor	Indoor	
8522/8519	3 years	5 years	2 years	5 years	1 year without
8522/8520					chemical strippers or tools

Warranty and Limited Remedy

The following is made in lieu of all other express or implied warranties, including any implied warranty of **merchantability** or fitness for a particular purpose or implied warranty arising out of a course of dealing, custom or usage of trade: all 3M products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the specifications stated in this Product Bulletin. 3M will replace or refund the price of any 3M materials that do not meet this warranty within the specified time periods. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor or non-3M materials charges.

See the Graphics Market Center Warranty Brochure, which gives the terms, additional limitations of the warranty, if any, and limitations of liability.

Graphic Construction Options

Opaque Graphics

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.

Viewer/Light Source



Overlaminate 8519, 8520 Adhesive on bottom

Imaging Media 8522 Image on top; adhesive on bottom

Opaque Substrate

Fabrication

Different combinations of shop temperature and humidity can affect the handling of the media, the protective finish and the printed graphic. For optimum performance, use the *middle* of each of these ranges whenever possible.

Shop Temperature

Acceptable: 60° to 95°F (15° to 35°C) Optimum: 65° to 73°F (18° to 23°C)

Shop Humidity

Acceptable: 20% to 80% Optimum: 45% to 60%

Condition the Media Before Use

These steps are especially important if you are operating outside the conditions recommended under Fabrication, above.

- · Leave the media in its original packaging until you are ready to condition and use it.
- The day before you need it, remove the media from the box and remove the plastic.
- Condition the media for 24 hours in the same environment as the printer.

Printer Settings for Optimum Quality

Refer to your Hewlett Packard printer manual for detailed operating instructions.

The quality of a printed image depends on a combination of factors: correct media selection, printing software and raster imaging processor (RIP), shop conditions, etc.

The printers qualified to use this media have print mode options that are programmed specifically for these media. Current charts that show the various modes and printing dpi, and the quality results you can expect are available at www.hp.com under the website's support section. We recommend that you print the same image at all of these settings to determine acceptable print and productivity results.

The highest quality settings are usually desirable for backlit applications.

The correct media selection makes most other necessary adjustments to the printer.

- For the HP DesignJet CP 2000 or 3000 series printers, select the Opaque Vinyl UV setting.
- For the HP Designjet 5000 series printers, select the 3M Changeable UV setting or the HP Durable Gloss UV or HP Colorfast Vinyl setting.
- For the Z series printers, refer to HP's website or printer manuals.

Note: The HP printer settings lay down less ink per pass, which results in better ink absorption and quicker drying times.

- For the HP DesignJet CP 2000 or 3000 series printers, select the Opaque Vinyl UV setting.
- For the HP Designjet 5000 series printers, select the 3M Changeable UV setting or the HP Durable Gloss UV or HP Colorfast Vinyl setting.
- · For the Z series printers, refer to HP's website or printer manuals.

Note: The HP printer settings lay down less ink per pass, which results in better ink absorption and quicker drying times.

Drying Guidelines

Usually, the media can be laminated within 10 minutes after printing. However, especially in high humidity conditions, we recommend waiting 15 to 30 minutes before laminating.


Use care when handling graphics that have not been laminated to avoid scratching and abrasion.

Graphics made with this media and ink combination typically may be wound directly on a take-up roll after printing.

Whether or not you want a warranted graphic, an overlaminate is recommended to enhance durability, especially in outdoor applications.

Overlaminate

FIGURE 1
Typical Laminator Thread-up



Creating a Laminated Overlap


Creating a laminated overlap helps ensure that the graphic does not peel or lift away from certain banner materials that may be subject to plasticizer migration. This method may also be used for flat, rigid or flexible sign applications.

- 1. Print the graphic as usual.
- 2. On all sides of the graphic, score the film only to the correct, final graphic dimension without cutting through the liner.

Weed away the excess film, leaving the bare liner exposed around the graphic. See FIGURE 2.

FIGURE 2 Trim and Weed Film Margin Only





Laminate the graphic as usual (see page 5), making sure that at least one inch of the bare liner is covered by the laminate. See FIGURE 3.